



NOTES:

- 1. TESTING: 100% OPEN AND SHORT TEST
- 2. ALL MATERIAL BE ROHS COMPLIANT

8	COVER	DMS 59P BLACK DUST COVER	1	
7	OVERMOLD	BLUE 45P PVC	A/R	
6	OVERMOLD	BLACK 45P PVC	A/R	
5	INNERMOLD	LD-PE	A/R	
4	SCREW	DMS 59P A WORD SCREW #4-40 TOOTH MATERIAL: FAST PIN STEEL; INSULATOR: BLACK	1	
3	CONN.	HDB 15P FEMALE ; CONTACT: G/F; INSULATOR: BLUE; SHELL: NI PLATED	2	
2	CONN.	DMS 59P MALE ; CONTACT: G/F; INSULATOR: BLACK; SHELL: NI PLATED	1	
1	CABLE	UL-2919 28#*3COAX+26#*4P+AE(#24)B(93%) T. C OD: 9.5mm BLACK PVC	2	
ITEM	NAME	DESCRIPTION	Q' TY	BEMARK

APPROVED	CHECKED	DRAWN	ITEM NO.	DMS59-2VGA
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

DMS59P---2*HDB 15P F

