



NOTES:

1. ALL COMPONENTS ARE RoHS COMPLIANT.
2. 100% OPEN AND SHORT TEST.
3. CONDUCTOR RESISTANCE: 3 OHMS
4. INSULATION RESISTANCE: 10 MEGOHMS.
5. HI-POT: DC200V/0.01S

| | | | |
|----|-------------|------|---|
| ④ | TAG | 1PCS | DELTACO TAG |
| ③ | HOOD MOLDED | 2PCS | BLACK PVC |
| ② | CONNECTOR | 2PCS | DISPLAYPORT 20P MALE GOLD PLATED |
| ① | CABLE | 1PCS | [(28AWGx1PAIR)+D+FAM]x5+(28AWGx4C)+ AB(128/28AWG ALM)+D7/0.16TC BLACK PVC JACKET OD:7.3±0.2mm |
| NO | PARTS NAMF | O'TY | SPFCIFICATION |

| | | | | |
|----------|---------|-------|-----------|-----------|
| APPROVED | CHECKED | DRAWN | CUSTOMER: | |
| | | | ITEM NO. | DP-1010-K |
| | | | DRAW NO. | |
| | | | UNIT | mm |
| | | | SCALE | NONE |

DESCRIPTION:

DISPLAYPORT CABLE 20P M/M

