



PIN OUT

| P1 | P2 |
|--------------------|----|
| 1 | 11 |
| 3 | 12 |
| 5 | 10 |
| 7 | 8 |
| 9 | 9 |
| 11 | 7 |
| 13 | 5 |
| 15 | 6 |
| 17 | 4 |
| 19 | 19 |
| 2 | 18 |
| 4 | 13 |
| 6 | 14 |
| 8 | 2 |
| 10 | 3 |
| 12 | 1 |
| 14 | 16 |
| 16 | 15 |
| 18 | 17 |
| 20 (no connection) | 20 |

NOTES:

1. ALL COMPONENTS ARE RoHS COMPLIANT.
2. 100% OPEN AND SHORT TEST.
3. CONDUCTOR RESISTANCE: 3 OHMS
4. INSULATION RESISTANCE: 10 MEGOHMS.
5. HI-POT: DC200V/0.01S

| | | | |
|-----|-------------|------|---|
| ⑤ | TAG | 1PCS | DELTAO TAG |
| ④ | HOOD MOLDED | 1PCS | WHITE PVC |
| ③ | CONNECTOR | 1PCS | MINI DISPLAYPORT 20P MALE GOLD PLATED |
| ② | CONNECTOR | 1PCS | DISPLAYPORT 20P MALE GOLD PLATED |
| ① | CABLE | 1PCS | [(34AWGx1PAIR)+D+FAM]x5+(34AWGx4C)+ AEB WHITE PVC JACKET OD:5.0+0.2mm |
| NO. | PARTS NAMF | Q'TY | SPFCIFICATION |

| APPROVED | CHECKED | DRAWN | CUSTOMER: | |
|----------|---------|-------|-----------|---------|
| | | | ITEM NO. | DP-1105 |
| | | | DRAW NO. | |
| | | | UNIT | mm |
| | | | SCALE | NONE |

DESCRIPTION:

MINI DISPLAYPORT CABLE 20P M
DISPLAYPORT 20P M

