


Back-UPS CS 350
 Part Number : BK350EI
 Availability : Eastern Europe : Middle East : Africa ,
 Western Europe



Product Overview

Description	APC Back-UPS, 350VA/210W, Input 230V/ Output 230V, Interface Port USB
General Features	Addl Surge Protected Outlets , Audible Alarms , Auto Diagnostic Testing , Hot Swap Batteries , Internet FAX - modem - DSL protection , Lightning and Surge Protection , Modem Protection , Software , Status Indicator LED's , Unattended Shutdown , User Replaceable batteries , USB compatible
Includes	CD with software , User Manual , USB cable

Technical Specifications

Output	
Output power capacity	350 VA
Output power capacity	210 Watts
Nominal output voltage	230 V
Waveform type	Stepped approximation to a sinewave
Output Connections	(3)IEC 320 C13  (1)IEC 320 C13 (Surge) (2)IEC Jumpers
Input	
Nominal input voltage	230 V
Input frequency	50/60 Hz +/- 5 Hz (manual switch)
Input Connection Type	IEC-320-C14 inlet
Input voltage range for main operations	196 - 280 V
Batteries	
Typical backup time at half load	22.2 minutes
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6 hour(s)
Replacement battery cartridge	(1) RBC2
Communications & Management	
Interface port	USB
Optional Software	Click here to view other Software options .
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rating	300 joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Physical	
Maximum height dimensions	3.60 inches (9.14 cm)
Maximum width dimensions	6.50 inches (16.51 cm)
Maximum depth dimensions	11.20 inches (28.45 cm)
Net weight	13.90 lbs (6.32 kg)
Shipping Weight	15.50 lbs (7.05 kg)
Shipping Height	7.00 inches (17.78 cm)
Shipping Width	9.50 inches (24.13 cm)
Shipping Depth	14.50 inches (36.83 cm)
Color	Beige
Environmental	
Operating Environment	0 - 40 °C (32 - 104°F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 m)
Storage Temperature	-15 - 45 °C (5 - 113°F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 m)
Audible noise at 1 meter from surface of unit	40 dBA
Online thermal dissipation	19 BTU/hr
Conformance	
Approvals	C-tick, CE, EN50091-1, EN50091-2, GOST, PCBC, VDE
Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : 100000 Euro, Lifetime : 50000 GBP