



Item No. 42589 Delock External Enclosure 2 x M.2 Key B SSD > USB 3.1 Gen 2 USB Type-CTM female with RAID

Description

The aluminium enclosure by Delock enables the installation of two M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop. When using more than one SSD, there is the possibility to use different RAID level.



Specification

- Connector:
- external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C[™] female internal: 2 x 67 pin M.2 key B slot
- Chipset: Asmedia ASM1352R
- Supports M.2 modules in format 2280, 2260 and 2242 with key B based on SATA
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- · Data transfer rate up to 6 Gbps
- · Supports RAID 0, RAID 1, JBOD, Port Multiplier
- LED indicator for RAID mode
- 1 x button for RAID setting
- Compliant with USB Attached SCSI Protocol (UASP) Rev. 1.0
- Hot Plug, Plug & Play
- Colour: grey
- Dimensions (LxWxH): ca. 125 x 77 x 15.5 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

Package content

- External enclosure
- Screws
- Cable USB-C[™] male to USB Type-A male, length ca. 50 cm
- User manual

Images



© 2017 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Additional Information

EAN: 4043619425891

Country of origin: China

Package: Retail Box







General	
function:	Hot Plug
	Plug & Play
Supported operating system:	Linux Kernel 4.2
	Mac OS 10.9
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
Supported module:	M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
Maximum height of the components on	1.5 mm application of double-sided assembled modules supported
the module:	
Interface	
External:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Internal:	2 x 67 pin M.2 key B slot
Technical characteristics	
Data transfer rate:	6 Gb/s
RAID function:	JBOD
	0
	0
	1
Physical characteristics	1
Physical characteristics Housing material:	1
	1 Port Multiplier
Housing material:	1 Port Multiplier Aluminium
Housing material: Length:	1 Port Multiplier Aluminium 125 mm