



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125V AC RMS
- 2. CURRENT RATING : 1.5A mp
- 3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
- 6. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 C.2
ISO/IEC 11801:2010 CLASS EA

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+85°
- 2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

- 1. RJ45 JACK LIFE: 750 TIMES MIN
- 2. IDC LIFE : 200 TIMES MIN

MATERIAL LIST:

⑦	Upper Panel Cover	1.2mm thickness Metall Panel with plastic powder cladding	1	
⑥	Bottom Panel	1.5mm thickness Metall Panel with plastic powder cladding	1	
⑤	RJ45 Jack	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	12	
④	PCB	1.6mm UL 94V0	2	
③	IDC BODY	Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B	12	
②	IDC PIN	Phosphor Bronze & Tinned	96	
①	IDC TERMINAL	For 22-24 AWG Cable	12	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

DEL LOCK® we move the world	
Title: 10" Patch Panel 12 Port Cat.6A 0.5 U grey	
Dat	2016 / 01 / 08
Unit	mm
Projection	
Rev	A
Item no.	43311
Barcode	4043619433117
File No.	88220