



Item No. 91710

Delock USB 3.0 Card Reader All in 1

Description

This card reader by Delock has four memory card slots and allows to read and write many different memory cards. The card reader can be connected to a PC or laptop via the USB Type-A interface.



Note

• Supports SD 4.0 (UHS-II) memory cards

Specification

- · Connectors:
- 1 x USB 3.0 Type Micro-B female >
- 1 x CF type II slot
- 1 x Micro SD slot
- 1 x SD / MMC slot
- 1 x MS slot
- Chipset: Realtek RTS5321
- Data transfer rate up to:

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Supports PIO, DMA, UDMA mode
- Supports UDMA 7
- Supports SD 3.0 (UHS-I), SD 4.0 (UHS-II)
- Dimensions (LxWxH): ca. 85 x 52 x 19 mm
- Hot Swap, Plug & Play
- · Supports following memory cards:

Slot 1 Compact Flash

CF I, CF II, Micro Drive

Slot 2 Micro SD

MicroSD, Micro SDHC, Micro SDXC, Micro SD UHS-I, Micro SD UHS-II, T-Flash, MMCmicro

Slot 3 Secure Digital / Multi Media Card

SD, SD High Capacity (SDHC), SD UHS-I, SD UHS-II, SDXC, miniSD, MMC, MMC plus,

MMCmobile*, RS-MMC

Slot 4 Memory Stick

MS, MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO MagicGate, MS PRO Duo, MS PRO-HG Duo, MS PRO-HG Duo, MS XC-HG Duo, MS XC Duo, MS Micro*, MS PRO-HG Micro*, MS HG Micro*, MS XC-HG Micro*, MS XC Micro*, M2*

*Adapter is required

Additional Information

EAN: 4043619917105

Country of origin: China

Package: Retail Box







System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.x.x
- PC or laptop with a free USB Type-A port

Package content

- USB 3.0 Card Reader All in 1
- USB 3.0 Type Micro-B to Type-A cable, length ca. 50 cm
- User manual

Images













General	
function:	Hot Swap
	Plug & Play
Supported operating system:	Linux ex Kernel 4.x.x Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
Supported memory card:	Micro SD
	Micro SDHC
	Micro SDXC
	SD SDHC
	SDXC
	CF I
	CF II
	Micro Drive
	Micro SD UHS-I
	Micro SD UHS-II
	T-Flash
	MMCmicro
	SD UHS-I
	SD UHS-II
	miniSD
	MMC
	MMC plus
	RS-MMC
	MS
	MS Pro
	MS Pro-HG
	Memory Stick XC
	MS Duo
	MS Pro MagicGate
	MS PRO Duo
	MS PRO-HG Duo
	MS XC-HG Duo MS XC Duo
Interface	IVIO AO DUO
Output:	1 x CF type II slot
Carpan	1 x Micro SD slot
	1 x SD / MMC slot
	1 x MS slot
Input:	1 x USB 3.0 Type Micro-B female
	,,





Technical characteristics	
Chipset:	Realtek RTS5321
Data transfer rate:	up to 5 Gbps
Physical characteristics	
Length:	85 mm
Width:	52 mm
Height:	19 mm