



Delock Adapter HDMI-A male > Displayport 1.2 female black

Description

This adapter by Delock enables you to connect e.g. a Displayport monitor through a free HDMI interface.



Specification

• Connector:

Input:

1 x High Speed HDMI-A 19 pin male

1 x USB type A male (power supply)

Output:

1 x Displayport 20 pin female

- Chipset: STDP2600
- Displayport 1.2 and High Speed HDMI specification
- High Speed HDMI receiver link rate up to 2.97 Gb/s per data pair
- Supports 3D displays
- Supports a resolution up to 4Kx2K @ 30 Hz; $1920 \times 1080 @ 120 Hz$ (depending on the system and the connected hardware)
- Supports Audio 7.1 channel up to 192 kHz sample rate
- Supports HDCP 1.3
- Gold-plated connector
- Colour depth:

RGB / YCC (4:4:4) - 16 bit colour

YCC (4:2:2 / 4:2:0) - 16 bit colour

• Power consumption:

operation: ca. 500 mW standby: ca. 25 mW

• Colour: black

- Cable length: ca. 24.5 cm (incl. connector)
- OS independent, no driver installation necessary

System requirements

- A free HDMI-A female port
- A free USB-A female port
- Monitor with a free Displayport interface
- One Displayport cable

Item No. 62667



EAN 4043619626670

Country of origin China

Package content

- Adapter HDMI to Displayport
- User manual

Package

• Retail Box





Images

