

# Delock HDMI Stereo / 5.1 Channel Audio Extractor 4K

## Description

This adapter can be used to extract the audio signal from an HDMI transmission. While the image signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) and analog (stereo) to other devices such as headphones or a surround receiver.



## Specification

- Connector:
  - Input:
    - 1 x HDMI A 19 pin female
    - 1 x DC Power 5 V
  - Output:
    - 1 x HDMI A 19 pin female
    - 1 x 3.5 mm 3 pin Stereo jack female (Stereo Audio)
    - 1 x TOSLINK (S/PDIF)
    - 1 x RCA (S/PDIF)
- Switchable between stereo (2.0) and surround (5.1)
- Compatible with High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8-bit), 1920 x 1080 @ 60 Hz (12-bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)
- Audio DAC CS4344, 24 bit / 192 kHz
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): 71 x 61 x 21 mm
- Length: power cable USB Type-A > DC ca. 50 cm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm

## System requirements

- A free HDMI A female port

## Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- USB power cable

## Item No. 62692

EAN: 4043619626922

Country of origin: China

Package: Box



- Power supply 5 V
- User manual

Images



General	
Specification:	HDCP 1.4 High Speed HDMI LPCM Dolby Digital DTS Audio
Interface	
Input:	1 x HDMI A 19 pin female 1 x 5 V DC female 3,5 mm x 1,35 mm
Output:	1 x HDMI A 19 pin female 1 x 3.5 mm 3 pin Stereo jack female 1 x TOSLINK 1 x RCA
Technical characteristics	
Chipset:	Cirrus CS4344
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Video bandwidth:	300 MHz
Physical characteristics	
Housing:	metal
Length:	71 mm
Width:	61 mm
Height:	21 mm
Power supply	
Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Output:	5 V / 1 A
Connector:	DC male 3,5 mm x 1,35 mm
Cable length:	1 m