

## Item No. 62899

# Delock External USB 3.1 Gen 1 Hub USB Type-A > 3 x USB Type-A + 2 Slot SD Card Reader

### Description

This USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by three USB Type-A connectors as well as two slots for SD and Micro SD memory cards. If the hub is connected to a computer with a USB 3.1 interface, a maximum current of 900 mA is divided between the USB ports and the card reader. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



### Specification

- Connectors:
  - 1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A male >
  - 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
  - 1 x SD slot
  - 1 x Micro SD slot
  - 1 x 5 V DC jack
- Chipset: Genesys Logic GL3520 (Hub), GL3224 (Card Reader)
- Data transfer rate up to:
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
  - 1. Slot Secure Digital**  
SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
  - 2. Slot micro Secure Digital**  
MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- USB cable directly on the hub (length ca. 15 cm)
- Dimensions (LxWxH): ca. 90 x 40 x 13 mm
- 1 x ferrite core
- Colour: black
- Plug & Play

### Specification of the power jack

- 5 V, ground outside, plus inside
- Dimensions:
  - inside: ø ca. 1.35 mm
  - outside: ø ca. 3.5 mm
  - length: ca. 9 mm
- Optional power cable: [Delock 82377](#)
- Optional power supply: [Navilock 41337](#)

### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.x / Kernel 4.x.x, Mac ex OS 10.9, Android ex 6.0

### Additional Information

EAN: 4043619628995

Country of origin: China

Package: Retail Box



- PC or laptop with a free USB Type-A port

### Package content

- Hub USB + card reader
- User manual

### Images



General	
function:	Plug & Play
Supported operating system:	Linux ex Kernel 2.6.x Linux ex Kernel 4.x.x Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac ex OS 10.9 Android ex 6.0
Interface	
Output:	3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female 1 x SD slot 1 x Micro SD slot 1 x 5 V DC jack
Input:	1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A male
Technical characteristics	
Chipset:	Genesys Logic GL3520 GL3224
Data transfer rate:	USB 3.1 Gen 1 up to 5 Gb/s
Physical characteristics	
Ferrite core:	1 x
Cable length:	15 cm
Connector finishing:	gold-plated
Length:	90 mm
Width:	40 mm
Height:	13 mm
Colour:	black