



NOTES:

1.ELECTRICAL PROPERTIES:

- 1.1 100% OPEN AND SHORT TEST
- 1.2 CONDUCTOR RESISTANCE: 5 OHMS
- 1.3 INSULATION RESISTANCE: 10 MEGOHMS
- 1.4 HI-POT: DC300V/0.01S
- 1.5 100% HDTV, BLUE PAY DVD TEST(1080P: 7M); (1080I: 10M,15M)
- 1.6 ALL CABLE PROCESS SHOULD BE CONTROLLED BY ATC TEST DEVICE.

2. ALL MATERIAL BE RoHS COMPLIANT.

| | | | |
|-----|------------|------|--|
| ⑧ | TAG | 1PCS | DELTACO TAG |
| ⑦ | CORE MOLD | 2PCS | BLACK PVC |
| ⑥ | CORE | 2PCS | OD*ID*L: 17.5*12*28.5mm |
| ⑤ | SCREW | 2PCS | #4-40 UNC, HOOD MOLDED: BLACK PVC |
| ④ | DVI HOOD | 2PCS | BLACK PVC |
| ③ | DVI(24+5)M | 1PCS | GOLD PLATED SHELL |
| ② | DVI(24+5)M | 1PCS | GOLD PLATED SHELL |
| ① | CABLE | 1PCS | (30AWG*1P+D+FAM)*7+(28AWG+S+FAM)*3+28AWG*1P+28AWG*5C+AEB OD:9.5mm BLACK PVC JACKET |
| NO. | PARTS NAME | Q'TY | SPECIFICATION |

| | | | | |
|----------|---------|-------|-----------|---------|
| APPROVED | CHECKED | DRAWN | CUSTOMER: | |
| | | | ITEM NO. | DVI-625 |
| | | | DRAW NO. | |
| | | | UNIT | mm |
| | | | SCALE | NONE |

DESCRIPTION:

DVI(24+5)MALE/MALE

