



PIN OUT

P1 P2



NOTES:

1.ELECTRICAL PROPERTIES:

- 1.1 100% OPEN AND SHORT TEST
- 1.2 CONDUCTOR RESISTANCE: 5 OHMS
- 1.3 INSULATION RESISTANCE: 10 MEGOHMS
- 1.4 HI-POT: DC300V/0.01S
- 1.5 100% HDTV, BLUE RAY DVD TEST(1080P)
- 1.6 ALL CABLE PRODUCTION PROCESS ARE CONTROLLED BY ATC TEST DEVICE.

2. ALL MATERIAL BE RoHS COMPLIANT.

NO.	PARTS NAME	Q' TY	SPECIFICATION
⑧	TAG	1PCS	HDMI® HIGH SPEED WITH ETHERNET TAG
⑦	TAG	1PCS	DELTACO TAG
⑥	MicroHDMI19M	1PCS	GOLD PLATED SHELL
⑤	HOOD MOLD	1PCS	BLACK PVC
④	HOOD MOLD	1PCS	BLACK PVC
③	INNER MOLD	1PCS	PE
②	HDMI 19M	1PCS	GOLD PLATED SHELL
①	CABLE	1PCS	(34AWG*1P+D+FAM)*5+34AWG*4C+AEB OD:4.5mm±0.2mm BLACK PVC JACKET HIGH SPEED HDMI® CABLE WITH ETHERNET

APPROVED	CHECKED	DRAWN	CUSTOMER:
			ITEM NO. HDMI-1013
			DRAW NO.
			UNIT mm
			SCALE NONE

DESCRIPTION:

HDMI 19PIN/M-Micro HDMI 19PIN/M

