



Enclosure

2.5 External Enclosure SATA 6 Gb/s / IDE HDD to USB 3.0

Description

This Delock aluminium enclosure enables you to install a 2.5 IDE or 2.5 SATA HDD with an installation height of up to 12.5 mm. The enclosure can be connected to two free USB ports of your notebook or PC, by using the included Y-USB cable. The second USB port will be used as power supply in case one port does not provide enough power. The enclosure supports the SATA 3 Gb/s and SATA 6 Gb/s specification, which enable a high data transfer rate, if the enclosure is connected to a USB 3.0 port. Using the button on the backside you can easily open the enclosure.

Images



SATA



IDE



Ref.	42494
EAN	4043619424948
Country of origin	China
Customs tariff number	84733080

Specification

- USB 3.0-micro interface
- For 2.5 hard drives: SATA 1.5 Gb/s, 3 Gb/s and 6 Gb/s HDD or SSD
IDE HDD
- Data transfer rate: USB 3.0 up to 5 Gb/s,
SATA up to 6 Gb/s
IDE up to 133 Mb/s
- Supports hard disk height: 9 mm and 12.5 mm
- Dimension (LxWxH): 135 mm x 82 mm x 21 mm
- Enclosure with full-PCB
- 5 blue LEDs indicate power and activity
- Hot Plug, Plug & Play

System requirement

- Windows XP/XP-64/Vista/Vista-64/7/7-64, Linux ex Kernel 2.6
- PC or notebook with two free USB ports

Package content

- 2.5 external enclosure, USB 3.0 data-/ power cable
- Screwdriver, screws
- User manual

Package

- Retail Box