


Model	QH-NW457DS-P
View	
Camera	
Solution	
Sensor/DSP	1/2.8" Exmor CMOS
Day/Night	ICR
Min. Illumination	0.01lux @F1.2,AGC on,0 lux with IR on
Lens	3.6mm/6mm Fixed Lens
IR LED	24Leds
IR Distance	3-20m
Electronic Shutter	1/20~1/30000s
Video	
Compression	H.264/M-JPEG
Max.image Resolution	1920x1080
Frame Rate	30fps @ 1080P
Bit Rate	Main Stream: 1000~12000kps Sub Stream: 512~2048kbps
Audio	
Compression	G.711
Talkback	YES
Network	
Protocol	TCP/IP, UDP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP, NTP
Compliance	ONVIF V2.4(1.02 backward compatible) CGI
PC Client and Browser	ISS, IE6.0 and above, Google Chrome, Mozilla Firefox, Mac Safari
Mobile phone	iPhone, iPad, Android
WIFI	NA
WIFI Encryption	NA
3G Network	NA
Interface	
Video Output	NA
Audio Input	NA
Audio Output	NA
Alarm Input	NA
Alarm Output	NA
LAN	1 RJ45 10M / 100M ethernet port
RS-485	/
Storage Interface	/
PIR	NA
Reset Button	NA
General	
Working Temperature	-10°C~ +50°C
Working Humidity	0% - 90%
Protection Level	IP66
Power Supply	12 VDC ± 10% PoE(802.3af)
Consumption	4.3W IR ON 2.7W IR OFF
Dimension	67*67*170mm
Weight	320g
Road,Futian,Shenzhen,China,518040 Tel: +86-755-8982 2999 Fax: +86-755-8982 2000	