



LINAN WEIMAI ELECTRON CO.LTD

Address: No.399 North HuanCheng Road Linan Hangzhou China www.weimaicable.com
Phone:0086-61077585 Mobile:0086-13758296286 Email: sales@weimaicable.com

Coaxial Cable RG59+2DC 95% Braiding 75ohm china manufacturer supplier

Item: WM-COAX-031

1) Construction

Center Conductor: 0.81±0.01mm Copper /CU
 Dielectric: 3.7±0.05mmFoam PE
 Shield: CCA Foil
 Braid Coverage: 128X0.12mmCCA Pitch 20 95%Coverage
 Jacket: 6.10±0.10mmPVC white/Black
 Power Lines: 2X7X0.38mm CCA
 Package: 100M/Roll 305M/Drum 1000ft/500ft/Pull Box

2) Characteristics

Sparker Test: 4000VAC
 Impedance: 75±3 Ohm
 Capacitance: 54±3pF/m
 Velocity of Propagation: 85%
 Return Loss: 20dB min (5-2300MHz)

3) Attenuation

Attenuation		[@68° F. (20° C.)]	
Frequency (MHz)	Max. (dB/100 ft.)	Frequency (MHz)	Max. (dB/100 ft.)
5	0.86	400	5.10
55	2.05	450	5.40
83	2.45	500	5.70
187	3.60	550	5.95
211	3.80	600	6.20
250	4.10	750	6.97
300	4.45	865	7.52
350	4.80	1000	8.12



LINAN WEIMAI ELECTRON CO.LTD

Address: No.399 North HuanCheng Road Linan Hangzhou China www.weimaicable.com
Phone:0086-61077585 Mobile:0086-13758296286 Email: sales@weimaicable.com

Coaxial Cable RG59+2DC 95% Braiding 75ohm china manufacturer supplier

Item: WM-COAX-031



Email: sales@weimaicable.com Skype: weimaicable wechat:13758296286