











## UNIVERSAL ACCESS, NO MATTER WHAT

Imagine a router that connects you to the Internet via just about any broadband source available, be it Fixed, Mobile or even WiFi; a router that was designed with your most important requirement in mind: Internet access! The Dovado TINY AC is the world's first true Universal Access Router; a highly versatile device that securely connects all of your devices online without much effort. Whether your home or office has access to ADSL, Fiber, 4G/3G or WiFi, the Dovado TINY AC works with all!

## SPOTBOOST™ INTERFACE CONNECTS YOU TO OTHER WIFI NETWORKS!

The Dovado SpotBoost<sup>TM</sup> feature allows your Dovado TINY AC router to scan for all of the available WiFi networks in its proximity. Such networks may include a friendly neighbor, a public hotspot, your hotel's WiFi, a mobile pocket router or even a smartphone running WiFi-tethering! SpotBoost<sup>TM</sup> WiFi-Tethering is available on either WiFi band, be it 2.4GHz or 5GHz. Once connected, all of your devices will be able to access the Internet via SpotBoost<sup>TM</sup> and operate securely within the Dovado TINY AC's own private network. As an added bonus, features such as Dynamic DNS, (embedded) VPN Client and Port Forwarding are also available over the SpotBoost<sup>TM</sup> interface.

## AWARD-WINNING 4G/3G USB MODEM & MOBILE HOTSPOT SUPPORT!

The Dovado TINY AC is the first commercially available 802.11ac router to offer support for the very broadest range of 4G/LTE and 3G USB Modems and Mobile Hotspot devices in the world; handling full Category 6 LTE throughput speeds (300Mbps 4G)! Support for the latest modems are introduced with each new firmware update, accompanied by plenty of handy features we know you'll enjoy! The Dovado TINY AC is shipped with support for over 300 such devices from over 20 different brands, along with a decade of optimized software. Thanks to the Dovado SmartUSB<sup>TM</sup> feature, the Dovado TINY AC offers the best track-record in uptime performance by electrically re-powering the inserted USB modem in case of failure to connect.

## **TECHNICAL SPECIFICATIONS**

**PHYSICAL** 

**POWER REQUIREMENTS ANTENNA TYPE** WEIGHT

External detachable (SMA connector) 2dBi 167g 12VDC, 1A (100-240V AC, 50/60Hz)

Dipole Dual-Band Antenna

**DIMENSIONS** 

32 x 90 x 115 mm POWER, WAN, LAN, WLAN, USB/SMS

**OVERVIEW** 

MOBILE BROADBAND

**FEATURES** 

WIFI CAPABILITIES AC750, based on 300Mbps 802.11bgn (2.4GHz) ROUTER FEATURES Multilingual Quick Setup Wizard

& 450Mbps 802.11ac (5GHz)

Supports 32 + 32 WiFi clients (Dual SSID) Dovado SpotBoost<sup>TM</sup> WiFi-Tethering interface allows tethering with other WiFi infrastructures

for Internet connectivity

Detachable dual-band antenna with great

indoor coverage

MAC Address Filtering for WLAN WEP 64/128 bit encryption WPA/WPA2 (TKIP/AES/Mixed)-PSK

WPA2 Enterprise (requires a RADIUS server)

**FIXED BROADBAND** Gigabit Ethernet connectivity, with full speed **FFATURES** 

throughput

Dynamic (DHCP) IP, Static IP, PPPoE

Authentication

Connect to other WiFi networks (as optional

WAN interface)

Automatic failover to mobile broadband or

WiFi-tethered network

Supports the widest range of 4G/3G USB

modems

Use your smartphone or Mobile Hotspot as a

modem (WiFi-pairing via Dovado SpotBoost<sup>TM</sup>) 4G/LTE routing speeds of 300 Mbps

Automatically configures Mobile Internet

settinas

Operates in Routed/Bridged mode\* Maximal uptime with  $SmartUSB^{TM}$  and

Connection Tracker $^{\text{TM}}$ 

Manual Selection of 4G/LTE Frequency Band\* SMS Mailbox/Remote Control/Notifications\*

Automatic failover between all Internet

connections

Port-Forwarding & Remote Management Bi-monthly Mobile Broadband Traffic

Counter

Multiple Dynamic DNS Clients

Internet Scheduler Port-Forwarding SPI-Firewall **UPnP** 

VPN Pass-through

Remote (Live) Firmware Updates via

HTTP/FTP/SMS Command

Email notifications (as alternative to SMS)

NTP Clock

**VPN FEATURES** PPTP-based VPN client (up to 128-bit MPPE

encryption)

VPN Phonebook (stored profiles)

Separate Port-Forwarding options for VPN

client

Host Exemptions (specify which devices use

VPN)

Dynamic DNS (own alias when using VPN)

Automatic redial in case of failure

**ENVIRONMENT** Operating Temperature: 0-40° Celsius

Operating Humidity: 10% to 90% (non-

condensing)

CERTIFICATIONS Type: CE

\*See www.dovado.com/modems for SMS & Bridge Mode compatibility

For more information, visit www.dovado.com

Tel. + 46 8 522 918 85 | Fax. + 46 8 522 918 86

E. sales@dovado.com | W. www.dovado.com

Dovado Europe AB Dovado FZ-LLC Knarrarnäsgatan 9 Al-Thuraya Tower 1 164 40 Kista P.O. Box 500422 Dubai

> T. +971 4 368 18 70 I F. +971 4 368 81 25 E. sales@dovado.com | W. www.dovado.com