



PIN OUT

|       |         |                    |
|-------|---------|--------------------|
| P1    | ————    | P2                 |
| 1     | ————    | 1 RED              |
| 2     | ———o——— | 2 WHITE            |
| 3     | ———o——— | 3 GREEN            |
| 4     | ————    | 4 BLACK            |
| SHELL | ————    | SHELL(BRAID+DRAIN) |

NOTES:  
 1. TESTING: 100% OPEN AND SHORT AND MISS WIRE TEST.  
 2. ALL MATERIAL ARE ROHS COMPLIANT.

|     |            |      |   |
|-----|------------|------|---|
| ⑥   | TAG        | 1PCS | DELTACO TAG                                       |
| ⑤   | HOOD MOLD  | 2PCS | BLACK PVC   |
| ④   | INNER MOLD | 1PCS | PE  |
| ③   | USB A F    | 1PCS | NICKEL PLATED SHELL                               |
| ②   | USB A M    | 1PCS | NICKEL PLATED SHELL                               |
| ①   | CABLE      | 1PCS | (26AWG*1P)+24AWG*2C+AEB OD:5.0mm BEIGE PVC JACKET |
| NO. | PARTS NAME | Q'TY | SPECIFICATION                                     |

|          |         |       |            |          |
|----------|---------|-------|------------|----------|
| APPROVED | CHECKED | DRAWN | CUSTOMER : |          |
|          |         |       | ITEM NO .  | USB2-102 |
|          |         |       | DRAW NO .  |          |
|          |         |       | UNIT       | mm       |
|          |         |       | SCALE      | NONE     |

DESCRIPTION :

USB A/M-USB A/F

