



NOTES:

- 1.TESTING:100%OPEN AND SHORT AND MISS WIRE TEST.
- 2.ALL MATERIAL ARE ROHS COMPLIANT.

PIN OUT

P1 ——— P2

- | | | |
|---|---|-------|
| 1 | 1 | RED |
| 2 | 2 | WHITE |
| 3 | 3 | GREEN |
| 4 | 4 | BLACK |

SHELL ——— SHELL(BRAID+DRAIN)

⑦	CORE	2PCS	BEIGE PVC OD*L:16.7*27.7mm
⑥	TAG	1PCS	DELTACO TAG
⑤	HOOD MOLD	2PCS	BLACK PVC
④	INNER MOLD	1PCS	PE
③	USB A F	1PCS	NICKEL PLATED SHELL
②	USB A M	1PCS	NICKEL PLATED SHELL
①	CABLE	1PCS	(26AWG*1P)+22AWG*2C+AEB OD:5.0mm BEIGE PVC JACKET
NO.	PARTS NAME	Q'TY	SPECIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	USB2-15F
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

USB A/M-USB A/F

