



Main

Range of product	Exxact
Product or component type	Electronic timer
Quantity per set	1 piece

Complementary

Wiring device mounting	Flush
Switch function	2-pole
Rated current	8 A 40 μ F capacitive 8 A with $\cos \varphi = 0.6$ inductive 8 A resistive
Rated voltage	230 V AC
Power range	1500 W 230 V AC halogen lamp 1840 W incandescent lamp 1000 W motor
Colour	White
Local signalling	Green LED indication in active position
Time delay	1 h 15 minutes 2 h 30 minutes 4 h 8 h
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid stranded cable(s) 1 x 1.5...2 x 2.5 mm ² solid cable(s)
Material	PC
Protection type	Electronic overload and temperature protection
Embedding depth	30 mm
Height	87 mm
Width	87 mm
Projecting depth	32 mm
Product compatibility	Complete with Exxact frame

Environment

Standards	EN 60669-1 EN 60669-2-1 IEC 60884-1 EN 60669-2-3
Product certifications	CE FIMKO NEMKO SEMKO
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available