

Item No. 12423

Delock GSM Antenna SMA plug 3.5 dBi fixed omnidirectional with magnetic base and connection cable (RG-174, 3 m) outdoor black

Description

This GSM antenna by Delock allows the usage of different GSM bands indoors and outdoors. It is compatible to UMTS, ZigBee 868 MHz / 915 MHz, DECT, Z-Wave and LoRa 868 MHz / 915 MHz.



Specification

- Connector: 1 x SMA plug
- Frequency range:
824 - 960 MHz
1710 - 2200 MHz
- UMTS, ZigBee 868 MHz / 915 MHz, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Antenna gain: 3.5 dBi
- Impedance: 50 Ohm
- Polarisation: vertical
- VSWR: 2.0
- Transmission power: 10 W
- Operating temperature: -30 °C ~ 70 °C
- Colour: black
- Antenna length including magnetic base: ca. 384 mm
- Cable: coaxial
- Cable type: RG-174
- Cable colour: black
- Cable attenuation: 1.5 dB @ 1.5 GHz per meter
- Cable diameter: ca. 2.7 mm
- Cable length incl. connector: ca. 3 m
- Diameter magnetic base: ca. 50.0 mm

Additional Information

EAN: 4043619124237

Country of origin: Taiwan, Republic of China

Package: Poly bag




System requirements

- Device with a free SMA jack

Package content

- GSM antenna

Images



General	
Mounting type:	magnet
Protection category:	without
Interface	
connector:	1 x SMA plug
Technical characteristics	
Frequency range:	824 - 960 MHz 1710 - 2200 MHz
Antenna gain:	3.5 dBi
Impedance:	50 Ω
Operating temperature:	-30 °C ~ 70 °C
Polarisation:	vertical
Power handling:	10 W
VSWR:	2.0
Physical characteristics	
Antenna type:	omnidirectional Rod antenna
Antenna length incl. magnetic base:	384 mm
Diameter magnetical base:	50 mm
Thread length:	8 mm
Cable type:	RG-174
Cable length incl. connector:	3 m
Diameter connector:	8.5 mm
Colour:	black
Thread type:	M5