

Delock HDMI Stereo / 5.1 Channel Audio Extractor

Description

This adapter can be used to extract the audio signal from an HDMI transmission. While the image signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) and analog (stereo) to other devices such as headphones or a surround receiver.



Specification

- Connector:
 - 2 x HDMI-A female (Input and Output)
 - 1 x 3,5 mm Stereo female (Stereo Audio)
 - 1 x TOSLINK (S/PDIF)
 - 1 x RCA (S/PDIF)
 - 1 x DC Power 5 V
- Switchable between stereo and 5.1 channel
- Compatible with HDMI 1080p, 3D and HDCP
- Video bandwidth up to 225 MHz / 2.25 Gb/s per channel, 6.75 Gb/s maximal
- Supports all common 2.0 und 5.1 audio formats (LPCM, DTS Digital, Dolby Digital, 32-192 kHz)
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): 70 x 60 x 20 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9 mm

Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- Power supply 5 V

Item no. 62492

EAN: 4043619624928

Country of origin: China

Package: Box



Images



