

# Delock HDMI Ethernet Extender Set by TCP/IP

## Description

This Delock HDMI Extender Set allows HDMI signals to be transmitted over a TCP/IP network. The transmitter and receiver can be connected with a network cable of up to 100 meters. Alternatively both devices can be connected via a switch, the distance between the HDMI source and the display device can then be 200 m.



## Specification

- Connectors (Sender and Receiver):
  - 1 x RJ45 jack
  - 1 x HDMI-A female
  - 1 x DC Power 5 V
- Following TCP/IP standard (Broadcasting)
- M-JPEG encoding / decoding up to 1080p / 60 Hz
- Supported resolutions:
  - 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Supports EDID und HDCP
- Video bandwidth up to 165 MHz / 1.65 Gb/s
- Optional: simultaneous operation of multiple receivers
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 103 x 84 x 25 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9 mm

## System requirements

- One HDMI cable to the HDMI source and display
- One Cat.5e or Cat.6 network cable
- Switch with VLAN or IGMP Snooping

## Package content

- HDMI Extender TCP/IP (Sender)
- HDMI Extender TCP/IP (Receiver)
- 2 x power supply
- User manual

## Item no. 65494

EAN: 4043619654949

Country of origin: China

Package: White Box



Images

