

## DS-T201-F



### Key Features

- 2 megapixel high performance CMOS
- Analog HD output, up to 1080p resolution
- Day/Night switch
- Smart IR
- Up to 20 m IR distance
- Switchable TVI/AHD/CVI/CVBS

## Specifications

| <b>Camera</b>        |   |
|----------------------|---|
| Image Sensor         | 2 MP CMOS Image Sensor  |
| Signal System        | PAL/NTSC  |
| Effective Pixels     | 1920 (H) × 1080 (V)   |
| Min. illumination    | 0.01 Lux@(F1.2,AGC ON), 0 Lux with IR   |
| Shutter Time         | 1/25 (1/30) s to 1/50,000 s   |
| Lens                 | 2.8 mm, 3.6 mm, 6 mm optional<br>Field of view: 103° (2.8 mm), 82.2° (3.6 mm), 54° (6 mm) |
| Lens Mount           | M12   |
| Day & Night          | ICR   |
| Angle Adjustment     | Pan: 0° to 350°, Tilt: 0° to 70°, Rotation: 0° to 350°                                    |
| Synchronization      | Internal synchronization  |
| Video Frame Rate     | 1080p@25fps/1080p@30fps   |
| HD Video Output      | 1 analog HD output  |
| S/N Ratio            | >62 dB  |
| <b>General</b>       |   |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)              |
| Power Supply         | 12 V DC ± 15%   |
| Power Consumption    | Max. 4 W  |
| IR Range             | Up to 20 m  |
| Dimension            | Φ 98 mm × 65.4 mm (3.86" × 2.57")   |
| Weight               | 240 g (0.53 lb.)  |

## Dimensions

