



# **PowerWalker SNMP Box**

**SNMP** Box

Monitor UPS through RJ45 network connection

RJ45 10/100BaseT port

Protocol support SNMP-V1, SNMP-V2

Supported MIB: RFC1213, RFC1628, MIB

Optional: Environmental Monitor Detector



Item-No. 10131000

PowerWalker SNMP Box is a communication solution for multiple UPS monitoring and control. Integrated web access will leverage internet capability of SNMP to remotely program or shut down UPSs. Equipped with SNMP Box, power conditions of all UPSs can be monitored anytime/anywhere even though the UPS units are located in different floors. Besides, this module also come equipped with easy-to-update firmware feature. Whenever the updated firmware is released, system manager can download it and simply upgrade all with one click. SNMP Box communicates with UPS via RS232 cable and it takes power supply via USB.

#### **Product Features**

- Allows controlling and monitoring of multiple UPSs through RJ45 network connection
- Real-time dynamic graphs of UPS data
- Warning notifications via audible alarm, broadcast, mobile messenger, e-mail and SNMP traps
- Historic data log stored in centralized PC database
- Simple firmware upgrade with one click
- Password security protection and remote access management
- ViewPower Pro software offers another enhanced communication solution for UPS monitoring and control.

### Supports following models:

VFI 1000, 1500, 2000, 3000 LCD VFI 1000C, 2000C, 3000C, 6000C, 10000C LCD VFI 1000RM, 1500RM, 2000RM, 3000RM, 6000R, 10000R LCD VFI 10000, 15000, 20000, 30000 CP 3/3





# **Technical Details**

#### **Product Features**

CPU	MCF52259	
System Clock	48.0M	
Flash memory	512K	
LED	3	
Watch Dog	YES	
SNMP Protocol	V1 and V2	
Supported MIB	RFC1213, RFC1628, MIB	
LAN Interface		
Туре	10M/100M UTP	
Ethernet Throughput	808 Kb/sec	
Latency	0.89 milliseconds	
Software & System Requirements		

Operating System	Windows family, Linux, Mac, Solaris
Other	1x RJ45 port
<b>Product Details</b>	
Dimensions	130mm x 72mm x 28mm
Colour	Black
Weight	200g
Model Code	PowerWalker SNMP Box
Environment	
Temperature	0°C – 40°C
Humidity	0 - 95% RH (non- condensing)
Package Conter	nt
Package Content	SNMP Box, manual
Optional	
EMD	Article-Nr. 10120544
Logistic Data	
Giftbox Language	EN
Manual Language	EN
Dimensions	176mm x 132mm x 42mm
Weight	360g
Item Number	10131000
EAN	4260074977424
Warranty	24 Months

#### Version: EN 07/05/2015

We reserve the right for technical changes and mistakes

# Integrated web access screenshot

P Web Server 2.0			Stat	us Logout Adm	inistrator
			ء 🗆	m	
Information	UPS information				
Status Basic information	UPS mode:	Standby Mode	UPS temp.:	18.8 °C	
	Auto reboot:	true	Converter mode:	false	
UPS setting	ECO Mode:	false	Bypass when UPS is off:	false	
arameters setting	Bypass not allowed:	false	Fault type:		
Control	UPS warning:				
teal-time control					
tem configuration	Input information				
Web E-mail	Input voltage:	233.6 V	Input frequency:	50.0 Hz	
SMS					
Wake on LAN	Output information				
Shutdown Event action	Output mornation Output voltage:	0.0.V	Output frequency:	0.0 Hz	
Scheduled	Output current:		Load level		
System time	Output current.	0.0 A	Load level.	0 /6	
NMP configuration					
Log	Battery information				
Event log Data log	Battery voltage:		Battery capacity:	90 %	
Help	Remaining backup time:	197 Min			
Serial Port Debug					
Senai Port Debug	EMD information				
	EMD temp.:	°C	Humidity:	%	

### Installation scenario

