

MALE - FEM. COMPRESSION "IEC" COAXIAL CABLE LEAD

HIGH SHIELDING, CLASS A+ AND LOW ATTENUATION






REF.	ART. NR	DESCRIPCIÓN	EAN 13
3852	TAK2015	CABLE LEAD COMPRESSION F - IEC WHITE 1.5m	4031136022150
385201	TAK2030	CABLE LEAD COMPRESSION F - IEC WHITE 3m	4031136022167
385202	TAK2050	CABLE LEAD COMPRESSION F - IEC WHITE 5m	4031136022174



A cable lead pre-terminated with compression IEC connectors, male at one end (ref. 3818) and female at the other end (ref. 3819), and made with a trishield Class A+ coaxial cable: the SK2000+ (ref. 4138xx).



REF.	ART. NR.	 m	 Grs	 Pack u.
3852	TAK2015	1.5	116	30
385201	TAK2030	3	198	20
385202	TAK2050	5	296	15



Ref. / Art.Nr.	3852xx / TAK20xx		
Cable type	Class A+		
Inner conductor	∅	mm	1.02
	Material	-	Cu (copper)
	Resistance	Ohm/Km	22
Dielectric	∅	mm	4.6
	Material	-	PEE (foam polyethylene)
Over lapped foil	Material	-	Aluminium + Polyester
	Material	-	CuSn (tinned copper)
Braid	Resistance	Ohm/Km	10.5
	Coverage	%	82
	2nd shielding film	-	Yes
Outer sheath	∅	mm	6.7
	Material	-	PVC (polyvinyle clorhidre)
Minimum bending radius	mm		33,5
Shielding at 1GHz	dB		>95 (typ. 125)
Capacitance	pF/m		54
Impedance	Ohm		75
Velocity ratio	%		84
Attenuations dB/m			
Frequency (MHz)	200		0.09
	500		0.14
	800		0.18
	1000		0.21
	1350		0.25
	1750		0.28
	2050		0.31
2300		0.32	