

## Features

- Compact size can be desktop or wall-mounted
- Excellent microprocessor control guarantees high reliability
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function
- 6 outlets
- Touch LCD screen (Option)
- USB communication port (Option)
- USB charger 5V/1A (Option)
- RJ11/RJ45 surge protection (Option)



## NanoFit STANDBY UPS SELECTION GUIDE

MODEL	NanoFit 600	NanoFit 800
<b>CAPACITY</b>	600VA / 360W	800VA / 480W
<b>INPUT</b>		
Voltage	220/230/240 Vac	
Acceptable Voltage Range	180-270 Vac	
Frequency Range	60Hz / 50Hz (Auto sensing)	
<b>OUTPUT</b>		
Voltage	220/230/240 Vac	
AC Voltage Regulation (Batt. Mode)	±10%	
Frequency Range (Batt. Mode)	60Hz or 50Hz ±1Hz	
Transfer Time	Typical 2-6 ms, Max. 10ms	
Waveform (Batt. Mode)	Simulated Sinewave	
<b>BATTERY</b>		
Battery Type & Number	12V / 4.5Ah x 1	12V / 5Ah x 1
Typical Recharge Time	8 hours recover to 90% capacity	
<b>INDICATORS</b>		
Line Mode	Green lighting	
Battery Mode	Yellow flashing	
Fault	Red lighting	
<b>ALARM</b>		
Battery Mode	Beeps every 10 seconds	
Low Battery	Beeps every second	
Overload	Beeps every 0.5 second	
Fault	Continuously beeping	
<b>PROTECTION</b>		
Full Protection	Overload, discharge, and overcharge protection	
<b>PHYSICAL</b>		
Dimension, D X W X H (mm)	305 x 158.5 x 95	
Net Weight (kg)	2.6	2.9
<b>ENVIRONMENT</b>		
Humidity	0-90 % RH @ 0- 40°C (non-condensing)	
Noise Level	Less than 40dB	

\* Product specifications are subject to change without further notice