



# devolo

## dLAN pro 1200 DINrail

### Technical data

<b>Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az, IEEE 802.1p Auto MDI/X
<b>Protocols</b>	CSMA/CA (Powerline)
<b>Transmission speeds</b>	Ethernet 10/100/1000 (mbps) Powerline 200/500/600/1200 (mbps)
<b>Modulation • Carrier</b>	Powerline OFDM - 4096/1024/256/64-QAM, QPSK, BPSK • Powerline 2880
<b>Range (in m)</b>	Powerline: 400
<b>Security</b>	128 Bit AES
<b>LEDs</b>	Power (on/off), Power (stand-by) PLC (Quality Indicator) ETH (link/activity)
<b>Buttons</b>	Pairing Reset Factory Default
<b>Device port</b>	3 x Phase, N, PE 1 x Ethernet RJ45
<b>Power consumption</b>	Maximum W/A: 4.5/0,020 Typical W/A: 3.3/0,014 Stand-By W/A: 0.7/0,003
<b>Power supply</b>	internal 196-250 V AC 50 Hz
<b>Temperature (Storage • Operating)</b>	-25°C to 70°C • 0°C to 40°C
<b>Dimensions (in mm, without plug)</b>	90 x 73 x 66
<b>Ambient conditions</b>	10-90% Humidity (non-condensing)
<b>Operating systems</b>	Windows 7 (32 Bit), Windows 7 (64 Bit) Windows 8.x (32 Bit), Windows 8.x (64 Bit), Windows 8.x Pro (32 Bit), Windows 8.x Pro (64 Bit) Ubuntu-Linux 12.04 (32 Bit) MAC OS X 10.6, MAC OS X 10.7, MAC OS X 10.8, MAC OS X 10.9
<b>Certifications</b>	CE Class B (EU, CH, NO)
<b>Additional features</b>	Master/Slave architecture



# devolo

## dLAN pro 1200 DINrail

### Sales information

<b>Warranty (in years)</b>	3
<b>Accessories</b>	Printed Install Flyer Ethernet Cable(s) CD-ROM with Manual and Software

### Single adapter

#### 9569 (EU)

**EAN:** 4250059695696  
**Weight:** 350 g  
**Dimensions:** 78.5 x 115 x 189 mm

WEEE additional information:

**Weight WEEE:** 230 g  
**Paper (Green Dot):** 80 g  
**Plastic (Green Dot):** 4 g  
**other (Green Dot):** 0.2 g