

## Item No. 62869

# Delock In-Desk Hub 3 Port USB 3.0 + 2 Slot SD Card Reader

### Description

This hub by Delock can be installed into an existing cut-out of the desk with a diameter of 60 mm or 80 mm to lead through the cables for the monitor, keyboard and mouse. At the same time, the hub offers three USB Type-A female ports and one SD Card Reader with two slots. The data transfer and power supply is guaranteed through one USB 3.0 Type-A male and one USB 2.0 Type-A male. The distance between the free connectors can be maximum 20 cm, because the two cables are connected with each other.



### Specification

- Connectors:
  - top side:
    - 3 x USB 3.0 Type-A female
    - 1 x SD slot
    - 1 x Micro SD slot
  - bottom side:
    - 1 x USB 3.0 Type-A male
    - 1 x USB 2.0 Type-A male (power supply)
- Chipset: VL813, GL3233
- Data transfer rate up to:
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
  - 1. Slot Secure Digital**  
SD, SD Pro, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, SDXC Ultra, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
  - 2. Slot micro Secure Digital**  
MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- Mounting diameter: 60 mm / 80 mm
- Mounting depth: 35 mm
- Cable length: ca. 95 cm
- Plug & Play

### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.x / Kernel 4.x.x, Mac OS 10.9 / Mac OS 10.12.1
- PC or laptop with two free USB Type-A ports
- 60 mm product and 80 mm cut-out of the desk

### Package content

- In-Desk Hub with Card Reader
- 60 mm ring
- 80 mm ring
- User manual

### Additional Information

EAN: 4043619628698

Country of origin: China

Package: Retail Box



Images



General	
function:	Plug & Play
Supported operating system:	Linux ex Kernel 2.6.x Linux ex Kernel 4.x.x Mac OS 10.9 Mac OS 10.12.1 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Supported memory card:	Micro SD Micro SDHC Micro SDXC SD SDHC SDXC T-Flash MMCmicro miniSD MMC RS-MMC MMC-I MMC-II MMC 4.0 MMCmobile RS-MMC 4.0
Interface	
Top side:	1 x Micro SD slot 1 x SD slot 3 x USB 3.0 Type-A female
Bottom side:	1 x USB 3.0 Type-A male 1 x USB 2.0 Type-A male (power supply)
Technical characteristics	
Chipset:	VL813 GL3233
Data transfer rate:	5 Gbps
Physical characteristics	
Cable length:	95 cm
Depth:	35 mm
Diameter:	80 mm 60 mm