



ART. 4925 Packaging Tape



- Ideal for manual and dispenser applications.
- Noisy Unwinding.
- Completely solvent free.

Material Informations		
Support	ВОРР	
Adhesive	Acrylic Water-Based	
Available Colours	Brown, Transparent, Yellowish, White	
Available Widths	38, 48, 50, 75 (mm)	
Available Lengths	50, 66, 100, 132, 180 (m)	

Technical Informations			
Support Thickness	25 mμ	± 3%	
Total Thickness	41 mµ	± 6%	
Adhesion to Steel Plate	>220 gr/cm	± 10%	
Tensile Strength	4,0 Kg/cm	± 10%	
Elongation	150%	± 10%	

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as avarage values of our standard production and cannot be taken as product specifications.

The products can present a ±2% tolerance in width and length.

We recommend all our customers to make sure that the products is acceptable through preliminary test.

Certified Systems
UNI-EN ISO 9001:2008 n° IT244111
UNI-EN ISO 14001:2004 n° IT246656
UNI-EN ISO 18001:2007 n° IT249944
REGISTRATION EMAS n°IT001596

ISO 9001
ISO 14001
OHSAS 18001

BUIREAU YERITAS
Certification

Revisited: 03/02/2015